844-1863 CHROMA-CHEM®YELLOW IRON OXIDE

Specification: 000000139827 Revision Date: 01-24-2017



Version Number: 06

1. Identification

Product identifier 844-1863 CHROMA-CHEM®YELLOW IRON OXIDE

Other means of identification

SAP Specification 000000139827

Recommended use Non-aqueous colorant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Chromaflo Technologies Corporation Company

> 2600 Michigan Avenue Ashtabula.OH 44005-0816

USA

Telephone 440-997-5137

Telefax 440-992-3613

NA: EMERGENCY # (3E) 866-519-4752 GLOBAL: EMERG. # (3E) (+1) 760-476-3962

3E CONTRACT # 12154 **3E ACCESS CODE** 334294 **CANADA: CANUTEC** 613-996-6666

EMERGENCY NUMBER

Product Regulatory

Services

ehs_americas@chromaflo.com

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Not classified. **Health hazards OSHA** defined hazards Not classified.

Label elements



Signal word

Hazard statement Flammable liquid and vapor.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Response

In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise None known.

classified (HNOC)

Material name: 844-1863 CHROMA-CHEM®YELLOW IRON OXIDE

If product is in liquid or paste form, hazards related to dust are not considered significant. But product may contain substances that could be potential hazards if caused to become airborne due to abrasive processes.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-methoxy-1-methylethyl acetate		108-65-6	20 - 40

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion Direct contact with eyes may cause temporary irritation. Most important

symptoms/effects, acute and delayed

Indication of immediate

medical attention and special treatment needed **General information**

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source

of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	
2-methoxy-1-methylethyl	TWA	50 ppm	
acetate (CAS 108-65-6)			

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

2-methoxy-1-methylethyl acetate (CAS 108-65-6)

Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection Respiratory protection not required. Use a NIOSH/MSHA approved respirator if there is a risk of

exposure to vapor/mist at levels exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Paste.
Physical state Liquid.
Form Liquid.
Color Yellow

Odor Sweet ether-like odor.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

> 289.4 °F (> 143 °C)

Flash point 116.0 °F (46.7 °C) Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Not available. Explosive limit - upper (%) Not available.

Vapor pressure Vapor density Not available.

1.65 Relative density

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Explosive properties Not explosive. Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the Conditions to avoid

flash point. Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Direct contact with eyes may cause temporary irritation. Eye contact

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Not known. Acute toxicity

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential No data available. No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN1263 **UN number**

Paint related material **UN proper shipping name**

Transport hazard class(es)

3 Subsidiary risk 3 Label(s) Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

B1, B52, IB3, T2, TP1, TP29 Special provisions

Packaging exceptions 150 173 Packaging non bulk Packaging bulk 242

DOT BULK

BULK

UN number UN1263

UN proper shipping name Paint related material

Transport hazard class(es)

Class 3

3 Label(s) Ш Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

B1, B52, IB3, T2, TP1, TP29 Special provisions

Packaging exceptions

Packaging non bulk 173 Packaging bulk 242

IATA

UN number UN1263

UN proper shipping name Paint related material

Transport hazard class(es)

Class 3
Subsidiary risk Packing group III
Environmental hazards No.
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Allowed with restrictions.

Passenger and cargo

aircraft
Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1263

UN proper shipping name Transport hazard class(es) PAINT RELATED MATERIAL

Class 3
Subsidiary risk Packing group III

Environmental hazards

Marine pollutant No. nS F-E, S-E

EmS F-E, S-E Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

DOT; DOT Bulk packaging type



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the US OSHA Hazard Communication

Standard and the Canadian Hazardous Products Regulation.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

> Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

WARNING: This product contains a chemical known to the State of California to cause cancer. **US** state regulations

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Silica, crystalline (quartz) (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
Taiwan	Taiwan Toxic Chemicals Substances Control Act	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

12-23-2013 Issue date **Revision date** 01-24-2017

Version # 06

Material name: 844-1863 CHROMA-CHEM®YELLOW IRON OXIDE

SDS US 7/8 000000139827 Version #: 06 Revision date: 01-24-2017 Issue date: 12-23-2013

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

The information contained herein is based on data believed to be reliable and the manufacturer disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.